

LA-UR-19-21043

Approved for public release; distribution is unlimited.

Title: Additive Manufacturing at Los Alamos National Laboratory: Part of a

Larger Vision

Author(s): Marchi, Alexandria Nicole

Intended for: Invited Talk to New Mexico Tech

Issued: 2019-02-07





EST.1943 -





Delivering science and technology to protect our nation and promote world stability

Additive Manufacturing at Los Alamos National Laboratory

Part of a Larger Vision



Alexandria Nicole Marchi, PhD


Materials Physics and Applications Division
Los Alamos National Laboratory
February 8, 2019



It's not the Destination, it's the Journey...

- Ralph Waldo Emerson or Lynn H. Hough (maybe)

2008-2014









1992-2001





s

2001-2003


- https://babymhospital.org/cardiothoracic-surgery.html
- https://sciencenotes.org/chemistry-jokes/
- http://labphoto.tumblr.com/post/128579102235/ bucket-chemistry-how-not-to-perform-a-reaction
- Rothemund, Nature (2006)
- 1663, March 2016

Photo Credit:

- www.Formlabs.com

Biochemistry Meets Nanotechnology: DNA Origami


M13mp18 viral ~250 unique strands designed to direct genome DNA, 7249-nt scaffold strand into desired shape





Organization for electrical or biomedical engineering

Single-electron transistor


Cell receptor organization










From Tylenol to Nuclear Security: Tamper Evident Seals Detect Access and Maintain Continuity of Knowledge











Top Down vs. Bottom up Manufacturing → Design Flexibility and Higher Detail

Subtractive Manufacturing

Feedstock:



Process:



Finished Part:



Additive Manufacturing








AM: Complex Design → Slicing → Feedstock and

Process Selection → **Post Processing**

Computer Aided

Design & Analysis



Slicing & **Tool Path** Determination

AM Process

Additive

Manufacturing


Component Inspection





AM Benefits: Full Design Freedom...Kinda

- Make complex shapes unattainable by other processes
- Internal cavities or passages
- Part count reduction (simpler assembly, less leak paths, etc)
- Combine materials and geometry to create parts with variable/tunable properties
- Tailored specialized parts
- Rapid production
- New design space!


















Fused Deposition Modeling (FDM): Thermoplastic

Extrusion through Heated Nozzle

Feedstock: Thermoplastic, Imbedded Powders












Mechanical Properties of Printed Parts are Anisotropic









Metal Printing: Laser or e-beam of Sintering Powder or Wire

Feedstock: Metal Powder, Metal Wire













Binderjet: Inkjet Printer Binds Powder




Polyjet: Photocurable Inkjet Drops


Feedstock: Photocurable Polymer



Stereolithography (SLA): First AM Process (1984)

Feedstock: Photocurable Resin






DLP Stereolithography Projects the Image onto the Resin

- High Speed Printing!

Feedstock: Photocurable Polymer





Basic Recipe of SLA Resin is Generally Simple

Monomers


Monomers Polymerize from Free Radical Photoinitiator

Photoinitiator

$$\begin{array}{c|c}
 & H_3C \\
 & O \\
 & O$$

Light Absorber to Optimize Printability


Absorber




AM is Not Perfect – The Problems are Opportunities

- Inaccurate geometry and poor surface finish
- Limited materials selection and uncertain properties
- Uncertain fabrication and reproducibility
- Thermal stresses within parts
- Slow production rate
- Small build size
- Post machining often required
- Machine variability











Successful AM Builds Requires New Design Thought **Processes**

Which part should be easier to build with DMLS?






Recognition of the Flaws in Each Print Method Facilitate **Print Success**

Thin-walled structures requiring support structure are difficult to fabricate with AM.




Limitations Should Lead to Cautious Optimism of AM

- Defect Prevention
- Empirical design rules
 - Overhangs
 - Infill
 - Features & Resolution
- Integrated parts and articulated parts
- Organic, Lattice, Cellular, Auxetic structures
- Topological optimization
 - Could produce a Ti part that is stronger but lighter than Al part




Clockwise from top left 30°, 22.5°, 15°, and 7.5° angled overhangs

Tooling & Fixtures



Forging & Casting Dies





Diagnostic Holders




Various Brackets



Concept or Functional Parts and Assemblies









Spectrometer



Complex Heat Exchangers




Water Skid Assembly



Prosthetics

Art and Jewelry





Construction



Food





Reverse Engineering

Optical Scanning to 3D Printing



Interest in Rapid Manufacturing is Growing Rapidly





Get Exited, Stay Flexible, Keep Options Open, Build your Network!